

Technische Daten

Technical specifications

		Fertigparkett Paneel	Sheets zum Verkleben Sheets for glue down
Beanspruchungsklasse nach Moisture load classification according to	EN 16511 EN 16511	Wohnbereich Kl. 23 Domestic use 23	Wohnbereich Kl. 23 Domestic use 23
Beanspruchungsklasse nach Moisture load classification according to	EN 16511 EN 16511	Objektbereich Kl. 32 Commercial use 32	Objektbereich Kl. 32 Commercial use 32
Gesamtstärke Total thickness	EN 428 EN 428	10 mm 10 mm	5 mm 5 mm
Rohgewicht Weight	EN 430 EN 430	8.400 g/m ² 8.400 g/m ²	3.150 g/m ² 3.150 g/m ²
Rohdichte Density		>600 kg/m ³ >600 kg/m ³	>550 kg/m ³ >550 kg/m ³
Format in mm Dimension in mm	EN 427 EN 427	Holz: 1235 × 200 wood: 1235 × 200	Holz: 1235 × 200 wood: 1235 × 200
		Stein: 620 × 450 stone: 620 × 450	Stein: 620 × 450 stone: 620 × 450
Abriebverhalten HotCoating® Abrasion resistance HotCoating®	EN 13329 EN 13329	AC5 AC5	AC5 AC5
Trittschallverbesserungsmaß Thermal insulation value	EN 140 EN 140	17 dB 17 dB	17 dB 17 dB
Brandverhalten Fire rating	EN ISO 9239-1 EN ISO 9239-1	CFL-S1 CFL-S1	CFL-S1 CFL-S1
Wärmedurchlasswiderstand Thermal insulation value	EN 12524 EN 12524	ca. 0,080 m ² K/W ca. 0,080 m ² K/W	ca. 0,063 m ² K/W ca. 0,063 m ² K/W
Maßstabilität Dimension stability	EN ISO 23999 EN ISO 23999	erfüllt passed	erfüllt passed
Resteindruck Indentation	EN 433 EN 433	max. 0,15 mm max. 0,15 mm	max. 0,25 mm max. 0,25 mm
Chemikalienbeständigkeit Chemical resistance	EN 423 EN 423	gut good	gut good
Lichtechtheit Light fastness	EN 485-B02 EN 485-B02	7-8 7-8	7-8 7-8
Stoßfestigkeit Impingement resistance	EN 51130 EN 51130	2.000 mm / 14 mm 2.000 mm / 14 mm	2.000 mm / 14 mm 2.000 mm / 14 mm
Stuhlrollenbeanspruchung Abrasion wear	EN 425 EN 425	geeignet Typ W pass typ W	geeignet Typ W pass typ W
Koeffizient Rutschhemmung Coefficient skid resistance	EN 51130 EN 51130	R10 R10	R10 R10
Emmissionswerte emmission values		laut AgBB in conformity with AgBB	laut AgBB in conformity with AgBB
Fußbodenheizung geeignet Underfloor heating suitable		ja (Warmwasser) yes (hot water)	ja (Warmwasser) yes (hot water)
Verlegung laying		uniclic ja uniclic yes	Vollflächige Verklebung glue down
Der Blaue Engel The Blue Angel			